



FineLine™ Series





FineLine™ Series

INTRODUCTION

Ideal's FineLine Series pavers are a smart choice for pavements where a refined, formal appearance is desired. Subtle chamfers along the edge create an easy-walk, easy-roll surface that is ideal for foot traffic and rolling apparatus such as wheelchairs, scooters, and carriages.

The square and rectangle shapes of the FineLine Series are proportionate in size and fit tightly together when assembled into a variety of laying patterns. Select from our popular Beacon Hill, Vineyard or Quarry Blends.

COMPOSITION & PERFORMANCE

Our FineLine pavers are manufactured under controlled factory conditions using specialized equipment that employs extreme pressure and vibration to mold carefully blended pure iron oxide pigments with a cement-rich mixture into high-density concrete pavers.

FineLine pavers offer superb quality, exceptional strength, and lasting durability. The units are dimensionally accurate, and possess a slip and skid resistant surface. They are unaffected by oil or gas spills and are resistant to NaCl type deicing chemicals applied at the proper rate and dosage.

The FineLine Series pavers are suitable for residential, commercial and municipal applications. Typical uses include walkways, patios, pool decks, sidewalks, courtyards, plazas, and pavements limited to personal vehicles. In the event underground repairs are necessary, the pavers can be removed and reinstated without leaving an unsightly patch.

TECHNICAL SERVICES

Please contact our office to obtain a copy of our Master Specification, as well as comprehensive technical information and literature.

Ideal is pleased to offer design consultation, specification assistance, and job-site quality review upon request.

A white deposit known as efflorescence may appear naturally on any concrete or masonry product. It does not effect the structural integrity and will dissipate over time. Efflorescence is not indicative of a flawed product. For more information, ask for Ideal's Efflorescence Advisory.

©2011-2015

FineLine™ Series is a trademark of Ideal Concrete Block Co.
Photography by N. Lawrence

PHYSICAL CHARACTERISTICS

FineLine Series pavers meet or exceed North American industry standards, including the requirements of ASTM Specification C 936 for Solid Concrete Interlocking Paving Stones and CSA Standards for freeze-thaw performance. Our strict quality control ensures consistent strength, color and size.

Nominal Size/Coverage:

Square: $6\frac{5}{16}" \times 6\frac{5}{16}"$ (160mm x 160mm) • 3.62 pcs/sf
Large Rectangle: $6\frac{5}{16}" \times 9\frac{7}{16}"$ (160mm x 240mm) • 2.42 pcs/sf
Grand Square: $9\frac{7}{16}" \times 9\frac{7}{16}"$ (240mm x 240mm) • 1.61 pcs/sf
Thickness: $2\frac{3}{8}"$ (6cm)

Compressive Strength: 8500 psi minimum

Water Absorption: 5% maximum


Freeze Thaw: No Effect

Slip Resistance: Excellent to ADA


DESIGN & CONSTRUCTION

Please see our *Contractor's Guide to Installing Interlocking Concrete Pavers* for comprehensive guidance on installation.


FineLine Series can be placed into an assortment of laying patterns including running bond, herringbone and select random patterns. Each size is packaged individually for greater design flexibility and choice. Mix and match just the right amount of each size to create a variety of patterns without having unneeded stones left over. When FineLine is bituminous set, the units can be set hand tight. When sand set, the units should be placed with $\frac{1}{16}"$ to $\frac{3}{16}"$ (2mm-5mm) joint widths.




Pattern 2
100 sf Rectangles




Pattern 3
100 sf Rectangles




Pattern 6
72.5 Rectangles
27.5 sf Squares



Pattern 20
75 sf Rectangles
25 sf Squares



GS Pattern 2
32 sf Rectangles
21 sf Squares
47 sf Grand Squares



GS Pattern 13
41 sf Rectangles
28 sf Squares
31 sf Grand Squares

45-55 Power Road, Westford, MA 01886
232 Lexington Street, Waltham, MA 02452

Main Phone: (781) 894-3200 • Main Fax: (978) 692-0817
www.IdealConcreteBlock.com

 **Pavers by
Ideal®**
A Registered Trademark of Ideal Concrete Block Co.