



## Town N' Country™ Pavers





# Town N' Country™ Pavers

## INTRODUCTION

Our Town N' Country™ collection of genuine tumbled pavers offers the look of natural stone cobbles, yet provides the quality, stability, and consistency of concrete pavers. Available in the weathered tones of our Vineyard, Quarry and Beacon Hill Blends, Town N' Country features Flip N' Place™ dual surfaces with a pronounced embossed face on one side and a "stone-rocked" finish on the other.

## COMPOSITION & PERFORMANCE




Town N' Country pavers are manufactured under controlled factory conditions using specialized equipment that molds a cement-rich mixture, carefully blended with pure, iron-oxide pigments, into high-density concrete pavers. Each Town N' Country paver undergoes our genuine Drum-Roll Tumbled™ process that imparts an aged finish and unique character to each piece, while preserving the structural integrity, strength, and durability found throughout our entire line of concrete pavers.

Town N' Country pavers are dimensionally accurate and offer a slip-resistant surface. Properly installed, they interlock to form a strong, snowplow-safe pavement suitable for residential, commercial, and municipal applications. Typical uses include walkways, driveways, patios, side-walks, courtyards, plazas, and pavements where traffic is limited to personal vehicles. In the event underground repairs are required, Town N' Country pavers can be taken up and reinstated without leaving an unsightly patch.

## PHYSICAL CHARACTERISTICS

Town N' Country pavers meet or exceed North American industry standards, including the requirements of ASTM Specification C 936 for Solid Concrete Interlocking Paving Stones and CSA Standards for freeze-thaw performance.

### Nominal Size/Coverage

-  Large Rectangle • 6<sup>5</sup>/<sub>16</sub>" x 9<sup>7</sup>/<sub>16</sub>" (160 x 240mm)  
2.42 pcs/sf
-  Square • 6<sup>5</sup>/<sub>16</sub>" x 6<sup>5</sup>/<sub>16</sub>" (160 x 160mm)  
3.62 pcs/sf
-  Grand Square • 9<sup>7</sup>/<sub>16</sub>" x 9<sup>7</sup>/<sub>16</sub>" (240 x 240mm)  
1.61 pcs/sf

**Thickness** 2<sup>3</sup>/<sub>8</sub>" (6cm) **Compressive Strength** 8500 psi min.  
**Freeze Thaw** No Effect **Water Absorption** 5% maximum  
**Slip Resistance** Excellent to ADA requirements

Town N' Country™ is a registered trademark of Ideal Concrete Block Co. ©2006-2020


## TECHNICAL SERVICES

Please contact our office to obtain a copy of our Master Specification, as well as comprehensive technical information and literature. Ideal is pleased to offer design consultation, specification assistance, and job-site quality review upon request.


## DESIGN & CONSTRUCTION

The design and construction of a Town N' Country pavement is the same as our other interlocking pavers. Each Town N' Country shape is packaged separately. Mix and match just the right amount of shapes and quantities you need for your project. Accent bands and border courses are easy to incorporate using our Flip N' Place dual surfaces. Please see our *Yankee Cobble™/FineLine™/MillStone™/Town N' Country™ Patterns with Style* for other patterns.


*Note: We recommend placing a sheet of woven geotextile fabric over the pavers to avoid scuffing the embossed surface when compacting.*




Pattern 2  
100sf Lg. Rectangles




Pattern 3  
100sf Lg. Rectangles




Pattern 6  
27.5sf Squares  
72.5sf Lg. Rectangles




Pattern 20  
25sf Squares  
75sf Lg. Rectangles




GS - Pattern 1  
69sf Grand Squares  
31sf Squares




GS - Pattern 2  
47sf Grand Squares  
32sf Lg. Rectangles  
21sf Squares



GS - Pattern 4  
19sf Grand Squares  
64sf Lg. Rectangles  
17sf Squares



GS - Pattern 8  
16sf Grand Squares  
84sf Lg. Rectangles



GS - Pattern 9  
43sf Grand Squares  
57sf Lg. Rectangles

*Magnesium, Potassium and Calcium Chlorides, including products that contain a blend of these chemicals, are NOT suitable deicers for concrete pavers. Please see our Deicing Advisory for detailed information.*

*Always wear proper safety equipment when cutting or sawing concrete products.*

*A white deposit known as efflorescence may appear naturally on any concrete or masonry product. It does not affect the structural integrity and will dissipate over time. Efflorescence is not indicative of a flawed product. For more information, ask for our Efflorescence Advisory.*



Traditional & Permeable Pavers ■ Landscape Retaining Walls ■ Natural Stone  
Manufactured by Ideal Concrete Block Co.  
45-55 Power Rd., Westford, MA 01886 ■ 232 Lexington St., Waltham, MA 02452  
(781) 894-3200 ■ info@IdealConcreteBlock.com ■ www.PaversbyIdeal.com