



Yankee Cobble™ Pavers





Yankee Cobble™ Pavers

INTRODUCTION

Cobblestones are as authentic to New England as the sailing ships that carried them as ballast across the Atlantic. In the days of horse and carriage, many of our cities used cobblestones to turn rutted dirt paths into paved streets. Today, Yankee Cobble™ pavers are the popular choice when a pavement featuring a natural stone appearance is desired.

COMPOSITION & PERFORMANCE

Yankee Cobble pavers offer superb quality, exceptional strength, and lasting durability. Manufactured under controlled factory conditions using a cement-rich blend and select aggregates, the units are saturated throughout with pure iron oxide pigments and molded into high density concrete pavers. Yankee Cobble features pressed corners and a dimpled texture that provides a turn-of-the-century look with the stability and uniformity of precision concrete pavers.

Yankee Cobble pavers are dimensionally accurate, offer a skid and slip-resistant surface, and when properly installed, are snow-plow safe. They resist deicing salts and are not degraded by oil and gas spills. In the event underground repairs are required, the stones can be lifted and reinstated without leaving an insightly patch. Yankee Cobble pavers are suitable for residential, commercial, and municipal pavement applications. Typical uses include walkways, driveways, patios, sidewalks, courtyards, plazas, and pavements where traffic is limited to personal vehicles.

PHYSICAL CHARACTERISTICS

Yankee Cobble pavers meet or exceed North American industry standards, including the strength, absorption, and freeze-thaw requirements of ASTM C 936 for Solid Concrete Interlocking Paving Stones. Our strict quality control ensures consistent strength, color and size.

Nominal Size/Coverage

Squares • 6⁵/₁₆" x 6⁵/₁₆" (160x160mm) • 3.62 pcs/sf

Large Rectangles • 6⁵/₁₆" x 9⁷/₁₆" (160x240mm) • 2.42 pcs/sf

Circle Pak • Creates circles 32"-108" in diameter

Thickness 2³/₈" (6cm)

Compressive Strength 8500 psi min.

Freeze Thaw No Effect

Water Absorption 5% maximum

Slip & Skid Resistance Excellent to ADA

Always comply with OSHA requirements on PPE and exposure limits when cutting or sawing concrete products.

Yankee Cobble™ is a trademark of Ideal Concrete Block Co. ©2006-2022



A Registered Trademark of Ideal Concrete Block Co.


TECHNICAL SERVICES

Please contact our sales office or visit our website at www.PaversbyIdeal.com for comprehensive technical information and literature. Ideal is pleased to offer design consultation, specification assistance, and job-site quality review upon request.


DESIGN & CONSTRUCTION

Yankee Cobble can create running bond, herringbone, and random pattern layouts. Yankee Cobble sizes are packaged individually for greater design flexibility and choice, allowing you to create a variety of patterns without having unnecessary stones left over. Mix and match just the right amount of Yankee Cobble shapes and quantities you need. Please see our *Yankee Cobble™ and MillStone™ Patterns with Style* for other patterns.


Note: Use a urethane pad when compacting to avoid scuffing the embossed surface.



Pattern 3
100 sf Lg. Rectangles



Pattern 4
60 sf Lg. Rectangles
40 sf Squares



Pattern 6
72.5 sf Lg. Rectangles
27.5 sf Squares



A white haze known as efflorescence may randomly appear on the surface of units. It does not affect the structural integrity and will dissipate over time. Because efflorescence is a natural by-product of cement hydration, its presence is not indicative of a flawed product and not covered under our warranty. For more information, please ask for our Efflorescence Advisory.

Magnesium, Potassium and Calcium Chlorides, including products that contain a blend of these chemicals, are NOT considered suitable deicers for concrete pavers. Please see our Deicing Advisory for detailed information.

Traditional & Permeable Pavers ■ Landscape Retaining Walls ■ Natural Stone
Manufactured by Ideal Concrete Block Co.
45-55 Power Rd., Westford, MA 01886 ■ 232 Lexington St., Waltham, MA 02452
(781) 894-3200 ■ info@IdealConcreteBlock.com ■ www.PaversbyIdeal.com